WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

A61N 5/06

(11) International Publication Number:

WO 97/46280

A1 |

(43) International Publication Date:

11 December 1997 (11.12.97)

(21) International Application Number:

PCT/SE97/00978

(22) International Filing Date:

4 June 1997 (04.06.97)

(30) Priority Data:

9602273-6

7 June 1996 (07.06.96)

SE

(71) Applicant (for all designated States except US): BIOLIGHT PATENT HOLDING AB [SE/SE]; Svärdvägen 15, S-182 33 Danderyd (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): THIBERG, Rolf [SE/SE]; Åkersbergavägen 10, S-184 50 Åkersberga (SE).

(74) Agents: ÖRTENBLAD, Bertil et al.; Noréns Patentbyrå AB, P.O. Box 10198, S-100 55 Stockholm (SE).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.


Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

In English translation (filed in Swedish).

(54) Title: DEVICE FOR EXTERNAL TREATMENT WITH PULSATING LIGHT OF HIGH DUTY CYCLE

(57) Abstract

Apparatus for external medical treatment with light, comprising a light-emitting device which is intended to lie against or to be held in the close proximity of the body of an individual, and a drive device for driving the lightemitting device, wherein the light-emitting device includes light-emitting diodes or corresponding elements and is adapted to emit monochromatic light of a first wavelength, wherein the drive device (8, 9, 10) is adapted to cause the lightemitting device (1) to emit the monochromatic light over a first predetermined time period in a first stage and thereafter emit selectively monochromatic light of a different wavelength than the first wavelength over a second predetermined time period in a possible second stage, and wherein the drive device (8, 9, 10) is adapted to cause the light-emitting device (1) to pulsate the emitted light in accordance with a predetermined pulse frequency or series of pulse frequencies over the time periods. The invention is characterized in that the drive device (8, 9, 10) is adapted to cause the light-emitting devices to emit the pulsating light with a pulse length that lies within an interval of about 60 % to 90 % of the time between respective start edges (18, 19) of two mutually sequential pulses (15).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

		States party to the PCT on the front pages of pamphlets publishing international appropriate states and the policy of the policy					
AL AM AT AU AZ BA BB BF BG BJ BR CA CF CG CH CI CM CN CU CZ DE	Albania Armenia Austria Austria Australia Azerbaijan Bosnia and Herzegovina Barbados Belgium Burkina Faso Bulgaria Benin Brazil Belarus Canada Central African Republic Congo Switzerland Côte d'Ivoine Cameroon China Cuba Czech Republic Germany	ES FI FR GB GE GH GN IL IS IT JP KE KG KP KR LC LI LK LR	Spain Finland France Gabon United Kingdom Georgia Ghana Guinea Greece Hungary Ireland Israel Iceland Italy Japan Kenya Kyrgyzstan Democratic People's Republic of Korea Republic of Korea Kazakstan Saint Lucia Liechtenstein Sri Lanka Liberia	LS LT LU LV MC MD MG MK ML MN MR MW NE NL NO NZ PL PT RO RU SD SE	Lithuania Luxembourg Latvia Monaco Republic of Moldova Madagascar The former Yugoslav Republic of Macedonia Mali Mongolia Mauritania Malawi Mexico Niger Netherlands Norway New Zealand Poland Portugal Romania Russian Federation Sudan Sweden	SI SK SN SZ TD TG TJ TM TR TT UA UG US VN YU ZW	Slovenia Slovakia Senegal Swaziland Chad Togo Tajikistan Turkmenistan Turkey Trinidad and Tobago Ukraine Uganda United States of America Uzbekistan Viet Nam Yugoslavia Zimbabwe

LR

Estonia

5

15

20

25

30

35

1

DEVICE FOR EXTERNAL TREATMENT WITH PULSATING LIGHT OF HIGH DUTY CYCLE

The present invention relates to apparatus for external medical treatment with light, and more specifically light that will alleviate and/or cure different sicknesses, illnesses, diseases, etc., hereinafter referred to as health disorders.

It has been found that infrared light has a favourable effect in this regard.

Swedish Patent Specification No. 502 784 teaches apparatus for external medical treatment with light, comprising a light-emitting device which is intended to lie against or be held in the close proximity of the body of an individual, and drive means for driving the light-emitting device, wherein the light-emitting device includes light-emitting diodes or corresponding light-emitting elements and is adapted to emit infrared light. The invention according to this patent is mainly characterized in that the drive device is adapted to cause the light-emitting device to emit light over a predetermined period of time in a first stage, and thereafter to emit visible light over a second predetermined period of time in a second stage; and in that the drive device is adapted to cause the light-emitting device to pulsate the emitted infrared light and the visible light respectively in accordance with a predetermined series of pulse frequencies.

It has been found that such apparatus can be used very successfully in the treatment of other disorders and injuries, for instance injuries sustained in sporting activities, pulled or strained muscles, muscular pain, joint pains, headaches, different inflammatory conditions, different skin complaints, such as acne, back pains, etc., provided that the light is emitted in a certain way. Treatment with light has a favourable effect on the healing of injuries and will alleviate and/or cure various health disorders.

WO 97/46280 PCT/SE97/00978

5

10

15

20

25

30

35

2

Thus, it is realized that treatment with light in which a certain light is emitted in a certain series of frequencies will have a significantly greater effect with respect to shortening the time taken to cure or alleviate a health disorder.

It has also been found that treatment with solely one or more monochromatic lights other than infrared light, such as visible light of different colours, emitted in accordance with a certain pulse frequency gives a very good treatment result.

The present invention is based on the insight that the pulse length of emitted pulsating light of a given pulse frequency has a great effect on the result of the treatment.

The present invention thus relates to apparatus for external medical treatment with light, wherein the apparatus includes a light-emitting device which is intended to lie against or to be held in the close proximity of the body of an individual, and a drive device for driving the light-emitting device, wherein the light-emitting device includes light-emitting diodes or corresponding elements and is adapted to emit monochromatic light of a first wavelength, wherein the drive device is adapted to cause the light-emitting device to emit said monochromatic light over a predetermined first time period in a first stage, and thereafter to emit selectively monochromatic light of a different wavelength to the first wavelength over a second predetermined time period in a possible second stage, and wherein the drive device is adapted to cause the light-emitting device to pulsate said emitted light in accordance with a predetermined pulse frequency or series of pulse frequencies over said time periods, and wherein the apparatus is characterized in that the drive device is adapted to cause the light-emitting devices to emit said pulsating light with a pulse length that lies within an interval of about 60% to 90% of the time WO 97/46280

3

between respective start edges of two mutually sequential pulses.

The invention will now be described in more detail with reference to exemplifying embodiments thereof and also with reference to the accompanying drawings, wherein

- Figure 1 illustrates the inventive apparatus schematically and in block form;
- 10 Figure 2 is a side view of a light-emitting device;
 - Figure 3 is a diagram; and
 - Figure 4 illustrates pulsated light.

Figures 1 and 2 illustrate apparatus for external medical treatment with the aid of light. The apparatus includes a 15 light-emitting device 1, which is intended to lie against or to be held in the close proximity of the body of an individual. Figure 2 shows the light-emitting device from one side, while Figure 1 shows the element from beneath. The lightemitting device includes a housing 5 which is provided with 20 a transparent plate 6. Located beneath the plate 6 is a surface 2 on which a plurality of light-emitting diodes 3, 4 or corresponding light-emitting elements are mounted. The light-emitting diodes send light through the plate 6 when the diodes are energized, i.e. supplied with current through a 25 cable 7. In use, the housing 5 is held so that the plate 6 will lie against the relevant part of the body. The apparatus also includes drive means 8, 9, 10 for driving the lightemitting device 1. The light-emitting device 1 may include light-emitting diodes 3 or corresponding means for emitting 30 infrared light. These diodes or the like are marked with solid circles in Figure 1.

The drive means 8, 9, 10 are adapted to cause the lightemitting device 1 to emit monochromatic light of a given wavelength over a predetermined time period. The drive means may also be adapted to emit monochromatic light of a wave5

10

25

30

35

4

length different to the first-mentioned wavelength over a second predetermined time period, in an optional second stage of the treatment. Visible light is emitted with the aid of light-emitting diodes 4 or corresponding elements. These diodes are marked with hollow circles in Figure 1.

The drive means 8, 9, 10 are also adapted to cause the lightemitting device 1 to emit pulsating light in accordance with a predetermined pulse frequency or a series of pulse frequencies over predetermined time periods. The drive means include a computer 8 which functions to control drive circuits 9, 10, to which voltage is applied for driving the light-emitting diodes via conductors 11, 12.

The computer and drive circuits are of an appropriate known kind. Connected to the drive means is a keyboard 13 by means of which the operator can enter drive means control data for actuating the light-emitting device in a desired manner. The apparatus will also conveniently include a display 14, on which the settings made through the keyboard are displayed.

Infrared light-emitting diodes 3 are preferably semi-conductor diodes of the GaAs kind (Gallium arsenide). The light-emitting diodes 4 that emit visible light are also preferably of the GaAs type.

For instance, the number of light-emitting diodes included in the light-emitting device may be such that the infrared light-emitting diodes will together generate a light power of 1800 milliwatts, and the diodes that emit visible light may each have a power of 3000 millicandela.

According to one embodiment of the invention, the lightemitting device 1 includes red light emitting diodes 4 that emit visible light at the wavelength of 660 nanometers and/or infrared light emitting diodes that emit light at the wavelength of 950 nanometers. WO 97/46280 PCT/SE97/00978

5

In another embodiment of the invention, the light-emitting device 1 includes light-emitting diodes 4 that emit a substantially monochromatic visible light in one of the colours violet, blue, yellow, orange, red or green.

5

15

The visible light used will depend on the disorder or type of injury to be treated.

The subject matter described above with reference to the accompanying drawings is essentially also found described in the aforementioned patent specification.

According to the invention, the drive device is adapted to cause the light-emitting device or elements to emit said pulsating monochromatic light at a pulse length that lies within an interval of about 60% to 90% of the time between respective start edges 18, 19 of two mutually sequential pulses 15.

- Figure 4 is a schematic illustration of emitted light pulses, where amplitude V is shown on the Y-axis and time t on the X-axis. The duration of a pulse 15 is referenced 16 and the total pulse time plus a subsequent pause is referenced 17.
- The medical effect per unit of time is shown on the Y-axis of the diagramme in Figure 3. This is a subjective measurement of the medical effect achieved, but is a result of tests of long duration and can therefore be considered highly reliable. The maximum value of the Y-axis is 100%. The X-axis shows the pulse length 16 as a percentage of the total time 17 of a pulse plus a subsequent pause, i.e. there is no pause between the pulses.
- As Figure 3 surprisingly shows, the curve has a maximum at a value of about 79% on the X-axis, whereafter the curve falls steeply to zero with respect to medical effect.

15

20

25

The treatment interval is therewith relatively narrow, and lies between 60% and 90% on the X-axis. A medical effect of at lowest 60% is obtained within this interval.

However, the interval is narrower in accordance with one preferred embodiment. According to this preferred embodiment, the pulse length lies within an interval of about 67% to 88% of the time between respective start edges of two mutually sequential pulses, i.e. from 67% to 88% on the X-axis. The medical effect is at lowest 80% within this interval.

It will be evident that realization of the circumstances reflected in Figure 3 are of the greatest significance in the external medical treatment of disorders and injuries with light. The present invention thus provides considerable advances in this field. It should be mentioned that application of the present invention is not restricted to the treatment of patients in accordance with the prior patent publication mentioned in the introduction but can also be applied in the acupuncture treatment of patients with light as described in Swedish Patent Specification No. 9602272-8.

The present invention is not therefore restricted to the aforedescribed and illustrated exemplifying embodiments thereof, since modifications and variations can be made within the scope of the following Claims.

WO 97/46280 PCT/SE97/00978

7

CLAIMS

Apparatus for external medical treatment with light, comprising a light-emitting device which is intended to lie against or to be held in the close proximity of the body of an individual, and a drive device for driving the lightemitting device, wherein the light-emitting device includes light-emitting diodes or corresponding elements and is adapted to emit monochromatic light of a first wavelength, wherein the drive device (8, 9, 10) is adapted to cause the light-emitting device (1) to emit said monochromatic light over a first predetermined time period in a first stage and thereafter emit selectively monochromatic light of a different wavelength than said first wavelength over a second predetermined time period in a possible second stage, and wherein the drive device (8, 9, 10) is adapted to cause the light-emitting device (1) to pulsate said emitted light in accordance with a predetermined pulse frequency or series of pulse frequencies over said time periods, characterized in that the drive device (8, 9, 10) is adapted to cause said light-emitting devices to emit said pulsating light with a pulse length that lies within an interval of about 60% to 90% of the time between respective start edges (18, 19) of two mutually sequential pulses (15).

25

20


5

10


15


2. Apparatus according to Claim 1, characterized in that the pulse length lies within an interval of about 67% to 88% of the time between the respective start edges of two mutually sequential pulses.














International application No. PCT/SE 97/00978

IPC
nents are included in the fields searched
practicable, search terms used)
ant passages Relevant to claim No
5, 1,2
fect of Therapy
nn
1-2 4 and
6 and
nt family annex.
lished after the international filing date or priority flict with the application but cited to understand
tlar relevance: the claimed invention cannot be
lar relevance: the claimed in the
or more other such documents, such combination erson skilled in the art
f the same patent family international search report
3 -09- 1997
, 41 (13)
fsson

INTERNATIONAL SEARCH REPORT

International application No. – PCT/SE 97/00978

	P	C1/3E 9//009/8
C (Continu	ation). DOCUMENTS CONSIDERED TO BE RELEVANT	
Category*	Citation of document, with indication, where appropriate, of the relevan	nt passages Relevant to claim No.
X	GB 2212010 A (AMCOR LTD), 12 July 1989 (12.07.8 see page 5, lines 25-34, page 7, lines 3-14 8, lines 19-35	9), 1 , page
A	US 5358503 A (DALE E. BERTWELL ET AL), 25 October 1994 (25.10.94), see column 5, 1 23-25 and claims	ines
A	US 5500009 A (EMANUEL MENDES ET AL), 19 March 1 (19.03.96), see column 2-3	1
		
A	US 5259380 A (EMANUEL MENDES ET AL), 9 November 1993 (09.11.93), see claim 11 ar column 5	1,2
A	WP 9519809 A1 (BIOLIGHT PATENT HOLDING AB), 27 July 1995 (27.07.95), see page 4 and cla	1,2
A	WO 9118646 A1 (OMEGA UNIVERSAL HOLDINGS LIMITED 12 December 1991 (12.12.91), see figure 2, 7-8 and claim 3)), 1 pages
A	WO 9519810 A1 (BIOLIGHT PATENT HOLDING AB), 27 July 1995 (27.07.95), see claims and page	ges 3-6

INTERNATIONAL SEARCH REPORT

Information on patent family members

01/09/97

International application No. PCT/SE 97/00978

200

Patent o	ent document in search report		Publication date	Patent family member(s)			dale
		 A1	05/05/77	FR 2:	329258	A,B	27/05/77
		 Al	26/11/92	NONE			
		A	12/07/89	IL	84367	A	27/02/94 15/04/97
GB 2	212010	Λ			102125		
		^	25/10/94		2181467		27/07/95 13/11/96
US 5	358503	Λ	to Cy = Cy =	Re-P	0741594 9519812		27/07/95
				. QW .	 3313017	. ^ 	
			19/03/96	0/1	2120457		28/03/95 09/11/93
us 5	500009	A	13, 00, 00		525938	A C	27/08/96
				US	554966	U A 	
			09/11/93	US	550000	9 A	19/03/96
US !	5259380	A	03/11/22	US	554966	0 A	27/08/96
	9519809		27/07/95	NONE			
			12/12/91	EP	048557	70 A	20/05/92
	9118646	A1 			154949	 95 A	08/08/95
WO	9519810) A1	27/07/95	AU AU	15494	95 A	08/08/95
				AU	61600		14/09/94
				BR	94060	91 A	12/12/95
				CA	21813	45 A	27/07/95 27/07/95
				CA	21813		25/12/96
				CN	11388		25/12/96 25/12/96
				CN	11388		13/12/95
				EP		145 A	06/11/96
				EP		567 A	06/11/96
				EP		568 A	25/08/95
				FI		017 A	08/10/96
				JP		468 T	24/08/95
				NO		333 A	11/12/95
				PL		399 A	15/01/96
				SE	502	784 C	23/12/96
				SE		298 C	21/07/95
				SE)153 A	21/07/95
				SE	_	2679 A	01/10/96
				SK		7095 A	27/07/95
				WO	951	9809 A	د., د., د